CONSTRUCTION PRODUCTS

DUAL PRESSURE WASHER - DPW2500/DPW 4000

Rotary Cleaner & Wand Pressure Washer in one machine



The MAKINEX DPW combines a rotary cleaner and wand pressure washer in the one machine, with the ease of swapping between them at the turn of a handle. The water pressure is fully adjustable up to 4000PSI on the DPW-4000 and up to 2500PSI on the DPW-2500, making it a powerful and versatile machine.

The versatility of the Makinex Dual Pressure Washer is unparalleled. The dual washer functions and adjustable water pressure make it perfect for heavy duty external cleaning applications including car parks, driveways, paths, paved areas, tennis courts, sports grounds, decks and more.

The integrated wand pressure washer can be used for cleaning applications including walls, fences, equipment and difficult to reach areas. Using the water pressure makes cleaning faster and saves water.

The Dual Pressure Washer is made from high quality components throughout and has a lifting eye and fold-down handle to assist with easy loading and transportation.

FEATURES & BENEFITS

- Easy handle to swap between rotary cleaner and wand functions
- Adjustable water pressure up to 4000PSI on the DPW-4000 and up to 2500PSI on the DPW-2500
- Stainless Steel surface rotary cleaner
- 10M high pressure hose with spiral guard
- Vibration reduction rubber engine mounts
- Thermal release valve
- Gearbox 2:1 reduction (1450RPM)
- Built in pressure gauge
- Inlet water filter
- Long-life, compact galvanised frame
- Easy manoeuvrability with front castors wheels
- Easy transport with lifting eye & foldable handles

SPECIFICATIONS DPW 2500

Weight		66kg (145lbs)	
Dimensions	L	1137mm (3ft 8.8in)	
(handle folde	ed) x W	/ 552mm (1ft 9.7in)	
	x	H 730mm (2ft 5in)	
Hose Length		10M (32ft 9in)	
Sound Level at handle		92dBa	
Engine	Pull	start Honda GX200	
	air-co	ooled 4 stroke OHV	
Fuel tank cap	bacity	3.1L (0.8 gallons)	
Fuel	Unleaded 86 octane or higher		
Pump	AR Triplex with gear reduction,		
thermal release valve & pressure guage			
Pressure ran	ge	1000-2500PSI	
Rotary size		530mm (21in)	

For more information contact your Makinex retailer: MTools Bergveste 26, 3992 DE Houten Telephone +31 6 24881203 Email: info@mtools.eu Website: www.mtools.eu

SPECIFICATIES DPW 4000

SPECIFICATIES D	FW 4000	
Weight	107kg (236lbs)	
Dimensions	L 1360mm (4ft 5.5in)	
(handle folded)	x W 620mm (2ft)	
	x H 890mm (2ft 11in)	
Hose Length	10M (32ft 9in)	
Sound Level at handle	92dBa	
Engine Elect	ric start Honda GX390	
əir	r-cooled 4 stroke OHV	
Fuel tank capacity	6.1L (1.61 gallons)	
Fuel Unleade	ed 86 octane or higher	
Pump Heavy duty AR Triplex with gea		
reduction, th	nermal release valve &	
pressure gu	lage & external bypass	
Pressure range	1000-4000PSI	
Rotary size	610mm (24in)	