

## DUAL PRESSURE WASHER – DPW2500/DPW 4000

### Rotary Cleaner & Wand Pressure Washer in one machine



The MAKINEX DPW combines a rotary cleaner and wand pressure washer in the one machine, with the ease of swapping between them at the turn of a handle. The water pressure is fully adjustable up to 4000PSI on the DPW-4000 and up to 2500PSI on the DPW-2500, making it a powerful and versatile machine.

The versatility of the Makinex Dual Pressure Washer is unparalleled. The dual washer functions and adjustable water pressure make it perfect for heavy duty external cleaning applications including car parks, driveways, paths, paved areas, tennis courts, sports grounds, decks and more.

The integrated wand pressure washer can be used for cleaning applications including walls, fences, equipment and difficult to reach areas. Using the water pressure makes cleaning faster and saves water.

The Dual Pressure Washer is made from high quality components throughout and has a lifting eye and fold-down handle to assist with easy loading and transportation.

#### FEATURES & BENEFITS

- Easy handle to swap between rotary cleaner and wand functions
- Adjustable water pressure up to 4000PSI on the DPW-4000 and up to 2500PSI on the DPW-2500
- Stainless Steel surface rotary cleaner
- 10M high pressure hose with spiral guard
- Vibration reduction rubber engine mounts
- Thermal release valve
- Gearbox – 2:1 reduction (1450RPM)
- Built in pressure gauge
- Inlet water filter
- Long-life, compact galvanised frame
- Easy manoeuvrability with front castors wheels
- Easy transport with lifting eye & foldable handles

#### SPECIFICATIONS DPW 2500

Weight	66kg (145lbs)
Dimensions	L 1137mm (3ft 8.8in)
(handle folded)	x W 552mm (1ft 9.7in)
	x H 730mm (2ft 5in)
Hose Length	10M (32ft 9in)
Sound Level at handle	92dBa
Engine	Pull start Honda GX200 air-cooled 4 stroke OHV
Fuel tank capacity	3.1L (0.8 gallons)
Fuel	Unleaded 86 octane or higher
Pump	AR Triplex with gear reduction, thermal release valve & pressure gauge
Pressure range	1000-2500PSI
Rotary size	530mm (21in)

For more information contact your Makinex retailer:

**Makinex Europe**  
**Rietdijk 4, 3994 AJ Houten**  
**Telephone +31 6 24881203**  
**Email: info@makinex.eu**  
**Website: www.makinex.eu**

#### SPECIFICATIONS DPW 4000

Weight	107kg (236lbs)
Dimensions	L 1360mm (4ft 5.5in)
(handle folded)	x W 620mm (2ft)
	x H 890mm (2ft 11in)
Hose Length	10M (32ft 9in)
Sound Level at handle	92dBa
Engine	Electric start Honda GX390 air-cooled 4 stroke OHV
Fuel tank capacity	6.1L (1.61 gallons)
Fuel	Unleaded 86 octane or higher
Pump	Heavy duty AR Triplex with gear reduction, thermal release valve & pressure gauge & external bypass
Pressure range	1000-4000PSI
Rotary size	610mm (24in)

